

Explosion proof Flow Computers when user-friendliness matters



Application examples: Salty Off-Shore conditions



Extreme cold weather at polar regions



Hot and sandy deserts

The E-Series provides unequalled safety and ease of use, opening covers is history. The through-glass keypad enables operability without interruptions. The E-Series saves time, money and hassle and delivers user-friendliness in the toughest conditions.

Advantages

- Save time and gain flexibility with the easy-to-operate through glass keypad: no need to remove the front cover or to arrange a work permit.
- Intuitive "Know one, know them all!" configuration menu, saving time, cost and aggravation.
- Cost saving with an easy to install, spacious chamber, plug and play connectors and 1" NPT thread for flow meter mounting.
- Durable high grade stainless steel 316L Ex d enclosure for extremely salty atmospheres (offshore).

Features

- Explosion proof according ATEX, IECEx, FM and CSA c-us.
- Data logging of flow rate, total and accumulated total.
- Easy configurable via PC with free downloadable software.
- Easy K-factor configuration for volumetric or mass.
- Display shows flow rate, total, acc. total, daily total, previous daily total, measuring units and a flow rate indicating speedometer.
- 7 digit flow rate / total and 11 digit accumulated total.
- Bright bi-color LED backlight.
- Ability to process all types of signals: Sine wave (coil), NAMUR, NPN/PNP pulse, Reed-switch, Active pulse signals, (O)4-20mA
- Modbus, HART or USB communication.
- Configurable pulse or alarm outputs and unscaled input retransmission.
- Analog (O)4 - 20mA output.
- Auto backup of settings and running totals.
- Power requirements: Loop powered, battery or 9 - 27V DC.
- Sensor supply: 8.2 / 12 / 24V DC.

Your success counts

Feature overview

- Solid die cast aluminum or high grade stainless steel 316L enclosure
- Flow rate indicating speedometer in percentage
- Display with bright backlight (65 x 45mm/2.56" x 1.77")
- Displayed function
- 11 digits (7mm, 0.28")
- Same configuration menu and keys as the F-Series: **"Know one, know them all!"**
- Side entry thread: 1/2"NPT / 3/4"NPT / M20 / M25
- USB connector via side entry
- Displayed function
- Engineering units
- 7 digits (12mm, 0.47")
- Easy-to-operate through glass keypad**
- Operational temperature: -40°C to +70°C (-40°F to 158°F)
- Bottom entry thread: 3/4"NPT / 1"NPT / M25



All info at a glance

Easy to install

Easy to program

Know one know them all!

Reliable

User-friendly